

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product form : Mixture
Product name : Aramid Fiber Reinforced Phenolic Laminate
Other means of identification : Gillfab 1360A Laminate
Gillfab 1360B Laminate

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Floor panels

1.3. Details of the supplier of the safety data sheet

The Gill Corporation
4056 Easy Street
El Monte, CA 91731
www.thegillcorp.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification (GHS-US)**

Carc. 1B H350
Repr. 1A H360
STOT SE 1 H370

Full text of H-phrases: see section 16

2.2. Label elements

Hazard pictograms (GHS-US) :



GHS08

Signal word (GHS-US) : Danger
Hazard statements (GHS-US) : H350 - May cause cancer
H360 - May damage fertility or the unborn child
H370 - Causes damage to organs
Precautionary statements (GHS-US) : P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P260 - Do not breathe dust/fume/gas/mist/vapors/spray
P264 - Wash ... thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P307 + P311 - If exposed: Call a poison center/doctor
P308 + P313 - If exposed or concerned: Get medical attention
P321 - Specific treatment (see Section 4 on this label)
P405 - Store locked up
P501 - Dispose of contents/container to comply with local/regional/national/international regulations

2.3. Other hazards

Other hazards not contributing to the classification : As packaged, this material does not present significant health hazards. The hazards below apply to the product if aerosols or dusts are generated from cutting, grinding, or smelting. As shipped this material is an inert Aramid fiber/plastic laminate in which ingredients have been cured using a thermoset process.

2.4. Unknown acute toxicity (GHS-US)

Not applicable

Aramid Fiber Reinforced Phenolic Laminate

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Aramid fiber (Poly(paraphenylenediamine))	(CAS No) 26125-65-1	55 - 75	Not classified
Co-cured phenolic resin/synthetic elastomer(containing Methanol, Phenol, Formaldehyde)	(CAS No) Proprietary	10 - 30	Carc. 2, H351 STOT SE 1, H370
Flame Retardant (containing styrene)	(CAS No) Proprietary	0.3-1.0	Carc. 1B, H350 Repr. 1A, H360

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Call 911 or emergency medical service. Move victim to fresh air. Keep victim warm and quiet. Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If exposed: Remove person to fresh air. If person is not breathing, provide artificial respiration. If necessary, provide additional oxygen once breathing is restored if trained to do so. Seek medical attention immediately.
- First-aid measures after skin contact : If minor skin irritation occurs, remove dust particles and wash affected area with soap and water. If irritation persists, seek medical attention.
- First-aid measures after eye contact : Immediately flush with large amounts of water, holding eyelids open, for at least 20 minutes. Repeat if necessary. Remove contact lenses, if present and easy to do. Seek medical assistance if irritation persists.
- First-aid measures after ingestion : Not an anticipated route of entry.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : As packaged, this material does not present significant health hazards. The hazards below apply to the product if aerosols or dusts are generated from cutting, grinding, or smelting.
- Symptoms/injuries after inhalation : Inhalation of dust may result in itching and upper respiratory tract irritation. Vapors may cause dizziness or suffocation.
- Symptoms/injuries after skin contact : Dusts and particulate matter may cause irritation of the skin.
- Symptoms/injuries after eye contact : Dusts and particulate matter may cause irritation of the eyes. Mechanical irritation, potentially severe, can result from eye contact with this material.
- Symptoms/injuries after ingestion : May cause toxic effects if inhaled or ingested/swallowed.
- Chronic symptoms : Persons with a history of chronic lung diseases may be at increased risk from exposure to excessive levels of nuisance dust. Persons with medical conditions generally aggravated by mechanical irritants in the air or on the skin may be at increased risk for a worsening of the underlying condition if exposed.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Any. Use media appropriate for surrounding fire.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Product will not burn.
- Explosion hazard : Can decompose in a fire emitting toxic fumes and gases of CO, CO₂, methane, formaldehyde, phenol, hydrogen bromide, and hydrogen cyanide, oxides of nitrogen, ammonia, and small amounts of aromatic and aliphatic hydrocarbons.

5.3. Advice for firefighters

- Firefighting instructions : Evacuate area.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Firefighters should wear a NIOSH approved full-face piece self-contained breathing apparatus (SCBA) operated in positive pressure mode and full turnout or bunker gear.
- Other information : If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

Aramid Fiber Reinforced Phenolic Laminate

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protective equipment. Avoid dust formation. Avoid breathing vapors, mist or gas. Avoid breathing dust.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Wear positive pressure self-contained breathing apparatus (SCBA). Wear protective clothing, a properly fitted, air-purifying or air-fed respirator if a risk assessment indicates this is necessary, chemical-resistant gloves, safety glasses.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Any wastes generated during cleanup operations should be evaluated with respect to hazardous and solid waste regulations and disposed of in a properly permitted facility in accordance with all local, state, and federal regulations.

6.3. Methods and material for containment and cleaning up

For containment : Do not walk through any dust resulting from damage to product. Prevent entry into waterways, sewers, basements or confined areas.

Methods for cleaning up : Pick up product and return to original packaging if reusable. If not reusable, place in appropriate containers for disposal. Any wastes generated during cleanup operations should be evaluated with respect to hazardous and solid waste regulations and disposed of in a properly permitted facility in accordance with all local, state, and federal regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with skin and eyes. Use methods to minimize dust. Do not breathe dust. DO NOT use compressed air or dry sweeping to remove dust from work area. Use a vacuum with adequate filtration system to remove dusts. If an appropriate vacuum is unavailable, only wet-clean-up methods should be used (i.e. misting). Moisture should be added as necessary to reduce exposure to airborne respirable dust.

Hygiene measures : Practice good housekeeping. Wash thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in tightly closed containers out of contact with the elements.

Incompatible products : Strong acids. reducing agents.

Packaging materials : Place carefully in dry, water-tight containers. Seal containers.

7.3. Specific end use(s)

Use of the substance/mixture : Floor panels

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Aramid fiber (Poly(paraphenylenediamine)) (CAS No) 26125-65-1

ACGIH	Not applicable
OSHA	Not applicable

Flame Retardant (containing styrene) (Not Available) Particulates Not Otherwise Regulated

ACGIH	Not applicable
OSHA	Not applicable

Co-cured phenolic resin/synthetic elastomer(containingMethanol, Phenol, Formaldehyde) (Proprietary)

ACGIH	Not applicable
OSHA	Not applicable

Particulates Not Otherwise Regulated (Total Dust)

ACGIH	ACGIH TWA (mg/m ³)	3 mg/m ³ Respirable; 10 mg/m ³ Total dust
-------	--------------------------------	---

Aramid Fiber Reinforced Phenolic Laminate

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Particulates Not Otherwise Regulated (Total Dust)

OSHA	OSHA PEL (TWA) (mg/m ³)	5mg/m ³ Respirable; 15 mg/m ³ Total dust
------	-------------------------------------	--

8.2. Exposure controls

Appropriate engineering controls	: General ventilation. Local exhaust and enclosed processes may be necessary for processes which generate large quantities of airborne dust.
Personal protective equipment	: An Appropriate apron or other body covering, see above, is recommended where there is a possibility of regular work clothing becoming contaminated with the product. All soiled or dirty clothing and personal protective equipment should be thoroughly cleaned before reuse.
Eye protection	: Where eye contact is possible with particulate matter, safety glasses with side shields are recommended.
Skin and body protection	: Use insulated, impervious plastic or neoprene-coated canvas gloves and protective gear (apron, face shield, etc.) to protect hands and other skin areas.
Respiratory protection	: If dusts or particulates are generated during handling or processing and exposures may exceed the limits cited above, use, as a minimum, a NIOSH approved ½ face piece respirator with cartridges approved for particulate matter with an exposure limit of not less than 0.05 mg/M3.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Flat Sheet.
Color	: Yellow
Odor	: Slight Sweet
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: 1.16g/cc
Solubility	: Unknown.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Product is stable. Hazardous polymerization will not occur.

10.3. Possibility of hazardous reactions

No additional information available

Aramid Fiber Reinforced Phenolic Laminate

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

Strong oxidizing agents, strong acids and bases, especially oxalic and hydrofluoric acid and acyl halides.

10.6. Hazardous decomposition products

CO, CO₂, formaldehyde, phenol, hydrogen bromide, hydrogen cyanide, oxides of nitrogen, ammonia and small amounts of aromatic and aliphatic hydrocarbons.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

Flame Retardant (containing styrene)

LC50 inhalation rat (mg/l)	2797 mg/l/4h
ATE US (vapors)	2797.000 mg/l/4h
ATE US (dust, mist)	2797.000 mg/l/4h

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Suspected of causing cancer.

Flame Retardant (containing styrene)

National Toxicology Program (NTP) Status	3 - Reasonably anticipated to be Human Carcinogen
--	---

Reproductive toxicity : Not classified
Specific target organ toxicity (single exposure) : Not classified
Specific target organ toxicity (repeated exposure) : May cause damage to organs (central nervous system, lung/respiratory system) through prolonged or repeated exposure (Dermal, Inhalation).
Aspiration hazard : Not classified
Symptoms/injuries : As packaged, this material does not present significant health hazards. The hazards below apply to the product if aerosols or dusts are generated from cutting, grinding, or smelting.
Symptoms/injuries after inhalation : Inhalation of dust may result in itching and upper respiratory tract irritation. Vapors may cause dizziness or suffocation.
Symptoms/injuries after skin contact : Dusts and particulate matter may cause irritation of the skin.
Symptoms/injuries after eye contact : Dusts and particulate matter may cause irritation of the eyes. Mechanical irritation, potentially severe, can result from eye contact with this material.
Symptoms/injuries after ingestion : May cause toxic effects if inhaled or ingested/swallowed.
Chronic symptoms : Persons with a history of chronic lung diseases may be at increased risk from exposure to excessive levels of nuisance dust. Persons with medical conditions generally aggravated by mechanical irritants in the air or on the skin may be at increased risk for a worsening of the underlying condition if exposed.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : This product has no known eco-toxicological effects.

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

Aramid Fiber Reinforced Phenolic Laminate

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: Disposal considerations

13.1. Waste treatment methods

- Waste disposal recommendations : If material as supplied becomes a waste, incinerate or landfill in accordance with local, state, and federal laws and regulations. Incinerate only if incinerator is operated at high temperature and is capable of scrubbing out acidic combustion products. Contact your local or state environmental agency for specific rules.
- Additional information : Empty containers will contain product residues. Observe proper safety and handling precautions. Do not allow empty containers to be used for any purpose except to store and ship original product.
- Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

- In accordance with DOT
Not regulated for transport

Additional information

- Other information : No supplementary information available.

ADR

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

Aramid Fiber Reinforced Phenolic Laminate

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

All components of this product are listed on the Toxic Substances Control Act (TSCA) inventory.

Aramid fiber (Poly(paraphenylenediamine))	CAS No	C \geq 55.00% ; C \leq 75.00%
Flame Retardant (containing styrene)	CAS No	C \geq 0.30% ; C \leq 0.10%
Co-cured phenolic resin/synthetic elastomer(containing Methanol, Phenol, Formaldehyde)	CAS No Proprietary	C \geq 10.00% ; C \leq 30.00%

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

Co-cured phenolic resin/synthetic elastomer(containingMethanol, Phenol, Formaldehyde) (Proprietary)

EPA TSCA Regulatory Flag : All components of this product are listed on the TSCA inventory.

15.2. International regulations

CANADA

Co-cured phenolic resin/synthetic elastomer(containingMethanol, Phenol, Formaldehyde) (Proprietary)

WHMIS Classification : Class B Division 2 - Flammable Liquid
Class D Division 2 Subdivision A - Very toxic material causing other toxic effects
Class D Division 2 Subdivision B - Toxic material causing other toxic effects

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

15.2.2. National regulations

15.3. US State regulations

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity

Aramid Fiber Reinforced Phenolic Laminate

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Flame Retardant (containing styrene)				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	Yes	No	


SECTION 16: Other information

Revision date : 09/20/2015
Data sources : ChemADVISOR, Inc. [<https://www.chemadvisor.com>]. GESTIS DNEL Database [[http://dnel-en.itrust.de/nxt/gateway.dll/dnel_en/000000.xml?f=templates\\$fn=default.htm\\$vid=dneleng:ddbeng\\$3.0/](http://dnel-en.itrust.de/nxt/gateway.dll/dnel_en/000000.xml?f=templates$fn=default.htm$vid=dneleng:ddbeng$3.0/)].

Full text of H-phrases:

Carc. 1B	Carcinogenicity Category 1B
Carc. 2	Carcinogenicity Category 2
Repr. 1A	Reproductive toxicity Category 1A
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
H350	May cause cancer
H351	Suspected of causing cancer
H360	May damage fertility or the unborn child
H370	Causes damage to organs

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.
NFPA fire hazard : 0 - Materials that will not burn.
NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating
Health : 3 - Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given
Flammability : 0 - Minimal Hazard
Physical : 0 - Minimal Hazard

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product