

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product form : Mixture
Product name : Fiberglass Reinforced Phenolic Adhesive Laminate
Other means of identification : Gillfab 1367P Laminate

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : The cargo liner is designed for use in the cargo compartment, bulkhead facings, and blowout panels for aircraft. Also used as backing material for non- textile floor mats used in wet areas of cabin interior (without Tedlar® overlay).

1.3. Details of the supplier of the safety data sheet

The Gill Corporation
4056 Easy Street
El Monte, CA 91731
www.thegillcorp.com

1.4. Emergency telephone number

Emergency number : CHEMTREC: 1-800-424-9300

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification (GHS-US)**

Acute Tox. 4 (Oral) H302
Acute Tox. 4 (Inhalation: dust, mist) H332
Skin Corr. 1B H314
Skin Sens. 1 H317
Muta. 2 H341
Carc. 1B H350
STOT RE 2 H373

Full text of H-phrases: see section 16

2.2. Label elements**GHS-US labeling**

Hazard pictograms (GHS-US) :



GHS05

GHS07

GHS08

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H302+H332 - Harmful if swallowed or if inhaled
H314 - Causes severe skin burns and eye damage
H317 - May cause an allergic skin reaction
H341 - Suspected of causing genetic defects (Dermal, Inhalation, oral)
H350 - May cause cancer (Dermal, Inhalation, oral)
H373 - May cause damage to organs (lung/respiratory system) through prolonged or repeated exposure (Inhalation)

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P260 - Do not breathe dust
P261 - Avoid breathing mist, dust, fume
P264 - Wash hands, forearms and face thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P271 - Use only outdoors or in a well-ventilated area
P272 - Contaminated work clothing must not be allowed out of the workplace
P280 - Wear face protection, protective gloves
P301 + P312 - If swallowed: Call a poison center/doctor if you feel unwell
P301 + P330 + P331 - If swallowed: rinse mouth. Do NOT induce vomiting
P302 + P352 - If on skin: Wash with plenty of water
P303 + P361 + P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower

Fiberglass Reinforced Phenolic Adhesive Laminate

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P304 + P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P308 + P313 - If exposed or concerned: Get medical advice/attention
P314 - Get medical advice/attention if you feel unwell
P321 - Specific treatment (See Section four (4) of this document on this label)
P330 - Rinse mouth
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention
P362+P364 - Take off contaminated clothing and wash it before reuse
P363 - Wash contaminated clothing before reuse
P405 - Store locked up
P501 - Dispose of contents/container to comply with local/regional/national/international regulations

2.3. Other hazards

Other hazards not contributing to the classification : As packaged, this material does not present significant health hazards. The hazards below apply to the product if aerosols or dusts are generated from cutting, grinding, or smelting. This product contains trace amounts of Nickel Antimony Titanium yellow pigment.

2.4. Unknown acute toxicity (GHS-US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Fiberglass	(CAS No) 65997-17-3	42 - 55	Carc. 1B, H350
Co-Cured Phenolic Resin/Synthetic Elastomer		25 - 35	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation: dust, mist), H332 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Muta. 2, H341 Carc. 1B, H350 STOT RE 2, H373
Acrylate Polymer	(CAS No) 9017-68-9	25 - 35	Not classified
Flame retardant		0.2 - 6	Not classified

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Call 911 or emergency medical service. Move victim to fresh air. Keep victim warm and quiet. Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If exposed: Remove person to fresh air. If person is not breathing, provide artificial respiration. If necessary, provide additional oxygen once breathing is restored if trained to do so. Seek medical attention immediately.

First-aid measures after skin contact : In case of burns, immediately cool affected skin for as long as possible with cold water. Do not remove clothing if adhering to skin.

First-aid measures after eye contact : Immediately flush with large amounts of water, holding eyelids open, for at least 20 minutes. Repeat if necessary. Remove contact lenses, if present and easy to do. Seek medical assistance if irritation persists.

First-aid measures after ingestion : Not an anticipated route of entry.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : As packaged, this material does not present significant health hazards. The hazards below apply to the product if aerosols or dusts are generated from cutting, grinding, or smelting.

Symptoms/injuries after inhalation : Inhalation of dust may result in itching and upper respiratory tract irritation. Vapors may cause dizziness or suffocation.

Symptoms/injuries after skin contact : Dusts and particulate matter may cause irritation of the skin. Contact with liquid on skin causes irritation and corrosion of tissue; continued exposure may cause dermatitis, chemical burns, and temporary loss of hair at site of contact.

Fiberglass Reinforced Phenolic Adhesive Laminate

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/injuries after eye contact	: Dusts and particulate matter may cause irritation of the eyes. Mechanical irritation, potentially severe, can result from eye contact with this material.
Symptoms/injuries after ingestion	: May cause toxic effects if inhaled or ingested/swallowed.
Chronic symptoms	: Persons with a history of chronic lung diseases may be at increased risk from exposure to excessive levels of nuisance dust. Persons with medical conditions generally aggravated by mechanical irritants in the air or on the skin may be at increased risk for a worsening of the underlying condition if exposed.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Any. Use media appropriate for surrounding fire.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Product will not burn.

5.3. Advice for firefighters

Firefighting instructions	: Evacuate area.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection. Firefighters should wear a NIOSH approved full-face piece self-contained breathing apparatus (SCBA) operated in positive pressure mode and full turnout or bunker gear.
Other information	: If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protective equipment. Avoid dust formation. Avoid breathing vapors, mist or gas. Avoid breathing dust.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Wear positive pressure self-contained breathing apparatus (SCBA). Wear protective clothing, a properly fitted, air-purifying or air-fed respirator if a risk assessment indicates this is necessary, chemical-resistant gloves, safety glasses.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Any wastes generated during cleanup operations should be evaluated with respect to hazardous and solid waste regulations and disposed of in a properly permitted facility in accordance with all local, state, and federal regulations.

6.3. Methods and material for containment and cleaning up

For containment	: Do not touch or walk through spilled material. Prevent entry into waterways, sewers, basements or confined areas.
Methods for cleaning up	: Pick up product and return to original packaging if reusable. If not reusable, place in appropriate containers for disposal. Any wastes generated during cleanup operations should be evaluated with respect to hazardous and solid waste regulations and disposed of in a properly permitted facility in accordance with all local, state, and federal regulations.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Good housekeeping and engineering practices should be employed to prevent the generation and accumulation of dusts. Wet mopping or vacuuming with a unit that contains a HEPA filter is recommended to clean up any dusts that may be generated during handling and processing.
Hygiene measures	: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store indoors in a cool, dry area to protect material and prevent premature polymerization.

Fiberglass Reinforced Phenolic Adhesive Laminate

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

- Incompatible products : Strong acids. Reducing agents.
Packaging materials : Place carefully in dry, water-tight containers. Seal containers.

7.3. Specific end use(s)

- Use of the substance/mixture : The cargo liner is designed for use in the cargo compartment, bulkhead facings, and blowout panels for aircraft. Also used as backing material for non- textile floor mats used in wet areas of cabin interior (without Tedlar® overlay).

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Fiberglass (65997-17-3)		
ACGIH	Not applicable	
OSHA	OSHA PEL (TWA) (mg/m ³)	3 fibers/cm ³ (fibers with diameter ≤ 3.5 μm & length ≥ 10 μm); 5 mg/m ³ TWA (total fibrous glass)

Co-Cured Phenolic Resin/Synthetic Elastomer (Not Available) Particulates Not Otherwise Regulated

ACGIH	Not applicable	
OSHA	Not applicable	

Flame retardant (Not Available) Particulates Not Otherwise Regulated

ACGIH	Not applicable	
OSHA	Not applicable	

Acrylate Polymer (9017-68-9) Particulates Not Otherwise Regulated

ACGIH	Not applicable	
OSHA	Not applicable	

8.2. Exposure controls

- Appropriate engineering controls : General ventilation. Local exhaust and enclosed processes may be necessary for processes which generate large quantities of airborne dust.
- Personal protective equipment : An Appropriate apron or other body covering, see above, is recommended where there is a possibility of regular work clothing becoming contaminated with the product. All soiled or dirty clothing and personal protective equipment should be thoroughly cleaned before reuse.
- Eye protection : Avoid contact with eyes. Use chemical safety goggles and/or a full face shield where splashing is possible.
- Skin and body protection : Use insulated, impervious plastic or neoprene-coated canvas gloves and protective gear (apron, face shield, etc.) to protect hands and other skin areas.
- Respiratory protection : If dusts or particulates are generated during handling or processing and exposures may exceed the limits cited above, use, as a minimum, a NIOSH approved ½ face piece respirator with cartridges approved for particulate matter with an exposure limit of not less than 0.05 mg/M3.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Solid
- Appearance : Flat Sheet.
- Color : Off white; brown
- Odor : Sweet
- Odor threshold : No data available
- pH : No data available
- Relative evaporation rate (butyl acetate=1) : No data available
- Melting point : No data available
- Freezing point : No data available
- Boiling point : No data available
- Flash point : No data available
- Auto-ignition temperature : No data available
- Decomposition temperature : No data available

Fiberglass Reinforced Phenolic Adhesive Laminate

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: 2.1
Solubility	: Unknown.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Product is stable. Hazardous polymerization will not occur.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

No additional information available

10.5. Incompatible materials

Strong oxidizing agents, strong acids and bases, especially oxalic and hydrofluoric acid and acyl halides.

10.6. Hazardous decomposition products

CO, CO₂, formaldehyde, phenol, toxic phosphorus compounds hydrogen fluoride, hydrogen cyanide, oxides of nitrogen, and small amounts of aromatic and aliphatic hydrocarbons.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed. Inhalation: dust/mist: Harmful if inhaled.

Fiberglass Reinforced Phenolic Adhesive Laminate

ATE US (oral)	1470.588 mg/kg body weight
ATE US (dust, mist)	4.412 mg/l/4h

Co-Cured Phenolic Resin/Synthetic Elastomer

ATE US (oral)	500.000 mg/kg body weight
ATE US (dust, mist)	1.500 mg/l/4h

Flame retardant

LD50 oral rat	> 3160 mg/kg
---------------	--------------

Skin corrosion/irritation	: Causes severe skin burns and eye damage.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Suspected of causing genetic defects (Dermal, Inhalation, oral).
Carcinogenicity	: May cause cancer (Dermal, Inhalation, oral).

Fiberglass (65997-17-3)

IARC group	3 - Not classifiable
National Toxicology Program (NTP) Status	3 - Reasonably anticipated to be Human Carcinogen

Flame retardant

IARC group	3 - Not classifiable
------------	----------------------

Fiberglass Reinforced Phenolic Adhesive Laminate

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: May cause damage to organs (lung/respiratory system) through prolonged or repeated exposure (Inhalation).
Aspiration hazard	: Not classified
Symptoms/injuries	: As packaged, this material does not present significant health hazards. The hazards below apply to the product if aerosols or dusts are generated from cutting, grinding, or smelting.
Symptoms/injuries after inhalation	: Inhalation of dust may result in itching and upper respiratory tract irritation. Vapors may cause dizziness or suffocation.
Symptoms/injuries after skin contact	: Dusts and particulate matter may cause irritation of the skin. Contact with liquid on skin causes irritation and corrosion of tissue; continued exposure may cause dermatitis, chemical burns, and temporary loss of hair at site of contact.
Symptoms/injuries after eye contact	: Dusts and particulate matter may cause irritation of the eyes. Mechanical irritation, potentially severe, can result from eye contact with this material.
Symptoms/injuries after ingestion	: May cause toxic effects if inhaled or ingested/swallowed.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : This product has no known eco-toxicological effects.

12.2. Persistence and degradability

No additional information available

12.3. Bio accumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

Additional information : Empty containers will contain product residues. Observe proper safety and handling precautions. Do not allow empty containers to be used for any purpose except to store and ship original product.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT

Not regulated for transport

Additional information

Other information : No supplementary information available.

ADR

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

Fiberglass Reinforced Phenolic Adhesive Laminate		
Listed on the United States TSCA (Toxic Substances Control Act) inventory		
Co-Cured Phenolic Resin/Synthetic Elastomer	CAS No	C>=25.00% ; C<=35.00%
Flame retardant	CAS No	C>=0.20% ; C<=6.00%
Acrylate Polymer	CAS No 9017-68-9	C>=25.00% ; C<=35.00%

Fiberglass Reinforced Phenolic Adhesive Laminate

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de Minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

15.2.2. National regulations

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm


SECTION 16: Other information

Revision date : 08/10/2015
Data sources : ChemADVISOR, Inc.[<https://www.chemadvisor.com>]. ChemIDplus [<http://chem.sis.nlm.nih.gov/chemidplus/rm/116094-23-6>]. GESTIS DNEL Database [[http://dnel-en.itrust.de/nxt/gateway.dll/dnel_en/000000.xml?f=templates\\$fn=default.htm\\$vid=dneleng:ddbeng\\$3.0/](http://dnel-en.itrust.de/nxt/gateway.dll/dnel_en/000000.xml?f=templates$fn=default.htm$vid=dneleng:ddbeng$3.0/)].

Full text of H-phrases:

Acute Tox. 4 (Inhalation: dust, mist)	Acute toxicity (inhalation: dust, mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Carc. 1B	Carcinogenicity Category 1B
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Flam. Liq. 3	Flammable liquids Category 3
Muta. 2	Germ cell mutagenicity Category 2
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Sens. 1	Skin sensitization Category 1
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
H226	Flammable liquid and vapor
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H332	Harmful if inhaled
H341	Suspected of causing genetic defects
H350	May cause cancer
H373	May cause damage to organs through prolonged or repeated exposure

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.
NFPA fire hazard : 0 - Materials that will not burn.
NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health : 3 - Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given
Flammability : 0 - Minimal Hazard
Physical : 0 - Minimal Hazard

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product