

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product form : Mixture  
Product name : Gillpatch III (Fiberglass Reinforced Cargo liner Patch)  
Other means of identification : Gillpatch III 6306 System

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Use of the substance/mixture : Gillpatch III is designed as a repair patch for holes and tears in all cargo compartment liners and damage to cargo containers. Also used in cargo areas where added reinforcement is desired (i.e. lower sidewall attaches points, floor). Gill patch III is approved for use in Class B, C and E cargo or luggage compartments as defined in FAR25.857.

**1.3. Details of the supplier of the safety data sheet**

The Gill Corporation  
4056 Easy Street  
El Monte, CA 91731  
[www.thegillcorp.com](http://www.thegillcorp.com)

**1.4. Emergency telephone number**

Emergency number : CHEMTREC: 1-800-424-9300

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification (GHS-US)**

Acute Tox. 4 (Oral)	H302
Acute Tox. 4 (Inhalation: dust, mist)	H332
Skin Corr. 1B	H314
Skin Sens. 1	H317
Muta. 2	H341
Carc. 1B	H350
STOT RE 2	H373

Full text of H-phrases: see section 16

**2.2. Label elements****GHS-US labeling**

Hazard pictograms (GHS-US) :



GHS05

GHS07

GHS08

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

H302+H332 - Harmful if swallowed or if inhaled  
H314 - Causes severe skin burns and eye damage  
H317 - May cause an allergic skin reaction  
H341 - Suspected of causing genetic defects (Dermal, Inhalation, oral)  
H350 - May cause cancer (Dermal, Inhalation, oral)  
H373 - May cause damage to organs (lung/respiratory system) through prolonged or repeated exposure (Inhalation)

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use  
P202 - Do not handle until all safety precautions have been read and understood  
P260 - Do not breathe dust  
P261 - Avoid breathing mist, dust, fume  
P264 - Wash hands, forearms and face thoroughly after handling  
P270 - Do not eat, drink or smoke when using this product  
P271 - Use only outdoors or in a well-ventilated area  
P272 - Contaminated work clothing must not be allowed out of the workplace  
P280 - Wear face protection, protective gloves  
P301 + P312 - If swallowed: Call a poison center/doctor/ if you feel unwell  
P301 + P330 + P331 - If swallowed: rinse mouth. Do NOT induce vomiting  
P302 + P352 - If on skin: Wash with plenty of water

# Gillpatch III (Fiberglass Reinforced Cargoliner Patch)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P303 + P361 + P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
P304 + P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing  
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P308 + P313 - If exposed or concerned: Get medical advice/attention  
P310 - Immediately call a doctor  
P312 - Call a poison center/doctor/... if you feel unwell  
P314 - Get medical advice/attention if you feel unwell  
P321 - Specific treatment (see Section four (4) of this document on this label)  
P330 - Rinse mouth  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention  
P362+P364 - Take off contaminated clothing and wash it before reuse  
P363 - Wash contaminated clothing before reuse  
P405 - Store locked up  
P501 - Dispose of contents/container to comply with local/regional/national/international regulations

### 2.3. Other hazards

Other hazards not contributing to the classification : As packaged, this material does not present significant health hazards. The hazards below apply to the product if aerosols or dusts are generated from cutting, grinding, or smelting. This product contains trace amounts of Nickel Antimony Titanium yellow pigment.

### 2.4. Unknown acute toxicity (GHS-US)

Not applicable

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Intumescent adhesive coating	(CAS No) Proprietary	35 - 41	Flam. Liq. 2, H225 Eye Dam. 1, H318
Fiberglass	(CAS No) 65997-17-3	31 - 35	Carc. 1B, H350
Co-cured phenolic resin/synthetic elastomer( containing Methanol, Phenol, Formaldehyde)	(CAS No) Proprietary	12 - 14	Carc. 2, H351 STOT SE 1, H370
Polyvinyl/fluoride polymer containing less than 0.025% nickel antimony titanium yellow pigment as nickel compounds	(CAS No) 24981-14-4	1 - 1.5	Carc. 1A, H350
Flame Retardant	(CAS No) Proprietary	0.4 - 0.7	Acute Tox. 4 (Oral), H302 Carc. 2, H351 Aquatic Acute 2, H401

Full text of H-phrases: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general : Call 911 or emergency medical service. Move victim to fresh air. Keep victim warm and quiet. Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If exposed: Remove person to fresh air. If person is not breathing, provide artificial respiration. If necessary, provide additional oxygen once breathing is restored if trained to do so. Seek medical attention immediately.

First-aid measures after skin contact : In case of burns, immediately cool affected skin for as long as possible with cold water. Do not remove clothing if adhering to skin.

First-aid measures after eye contact : Immediately flush with large amounts of water, holding eyelids open, for at least 20 minutes. Repeat if necessary. Remove contact lenses, if present and easy to do. Seek medical assistance if irritation persists.

First-aid measures after ingestion : Not an anticipated route of entry.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : As packaged, this material does not present significant health hazards. The hazards below apply to the product if aerosols or dusts are generated from cutting, grinding, or smelting.

Symptoms/injuries after inhalation : Inhalation of dust may result in itching and upper respiratory tract irritation.

Symptoms/injuries after skin contact : Dusts and particulate matter may cause irritation of the skin.

Symptoms/injuries after eye contact : Dusts and particulate matter may cause irritation of the eyes. Mechanical irritation, potentially severe, can result from eye contact with this material.

# Gillpatch III (Fiberglass Reinforced Cargoliner Patch)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Symptoms/injuries after ingestion	: May cause toxic effects if inhaled or ingested/swallowed.
Chronic symptoms	: Persons with a history of chronic lung diseases may be at increased risk from exposure to excessive levels of nuisance dust. Persons with medical conditions generally aggravated by mechanical irritants in the air or on the skin may be at increased risk for a worsening of the underlying condition if exposed.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Any. Use media appropriate for surrounding fire.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Product will not burn.
Explosion hazard	: Can decompose in a fire emitting toxic fumes and gases of CO, CO <sub>2</sub> , toxic phosphorus oxides, hydrogen fluoride, hydrogen cyanide and oxides of nitrogen.

### 5.3. Advice for firefighters

Firefighting instructions	: Evacuate area.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection. Firefighters should wear a NIOSH approved full-face piece self-contained breathing apparatus (SCBA) operated in positive pressure mode and full turnout or bunker gear.
Other information	: If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protective equipment. Avoid dust formation. Avoid breathing vapors, mist or gas. Avoid breathing dust.

#### 6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

Protective equipment : Wear positive pressure self-contained breathing apparatus (SCBA). Wear protective clothing, a properly fitted, air-purifying or air-fed respirator if a risk assessment indicates this is necessary, chemical-resistant gloves, safety glasses.

Emergency procedures : Ventilate area.

### 6.2. Environmental precautions

Any wastes generated during cleanup operations should be evaluated with respect to hazardous and solid waste regulations and disposed of in a properly permitted facility in accordance with all local, state, and federal regulations.

### 6.3. Methods and material for containment and cleaning up

For containment : Do not walk through any dust resulting from damage to product. Prevent entry into waterways, sewers, basements or confined areas.

Methods for cleaning up : Pick up product and return to original packaging if reusable. If not reusable, place in appropriate containers for disposal. Any wastes generated during cleanup operations should be evaluated with respect to hazardous and solid waste regulations and disposed of in a properly permitted facility in accordance with all local, state, and federal regulations.

### 6.4. Reference to other sections

No additional information available

# Gillpatch III (Fiberglass Reinforced Cargoliner Patch)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Note that the instructions for the correct use of this product prohibit sawing, grinding, milling, routing, or drilling of this material; only shearing or cutting by a knife blade may be used, essentially eliminating dust as a source of exposure.

Avoid contact with skin and eyes. Use methods to minimize dust. Do not breathe dust. DO NOT use compressed air or dry sweeping to remove dust from work area. Use a vacuum with adequate filtration system to remove dusts. If an appropriate vacuum is unavailable, only wet-clean-up methods should be used (i.e. misting). Moisture should be added as necessary to reduce exposure to airborne respirable dust.

Hygiene measures : Practice good housekeeping. Wash thoroughly after handling.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in tightly closed containers out of contact with the elements.

Incompatible products : Strong acids. Reducing agents.

Packaging materials : Place carefully in dry, water-tight containers. Seal containers.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Gillpatch III (Fiberglass Reinforced Cargo liner Patch)		
ACGIH	Not applicable	
OSHA	Not applicable	
Fiberglass (65997-17-3)		
ACGIH	Not applicable	
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	3 fibers/cm <sup>3</sup> (fibers with diameter ≤ 3.5 μm & length ≥ 10 μm); 5 mg/m <sup>3</sup> TWA (total fibrous glass)
Co-cured phenolic resin/synthetic elastomer (containing Methanol, Phenol, Formaldehyde) (Proprietary)		
ACGIH	Not applicable	
OSHA	Not applicable	
Polyvinyl/fluoride polymer containing less than 0.025% nickel antimony titanium yellow pigment as nickel compounds (24981-14-4)		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> Total dust, 1 fiber/cc Respirable, 0.2 mg/m <sup>3</sup> Insoluble; 0.1 mg/m <sup>3</sup> Soluble
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup> Respirable, 1 mg/m <sup>3</sup> Insoluble; 1 mg/m <sup>3</sup> Soluble
Flame Retardant (Proprietary)		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup> Respirable
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	5mg/m <sup>3</sup> Respirable
Intumescent adhesive coating (Proprietary)		
ACGIH	Not applicable	
OSHA	Not applicable	
Particulates Not Otherwise Regulated (Total Dust)		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup> Respirable; 10 mg/m <sup>3</sup> Total dust
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	5mg/m <sup>3</sup> Respirable; 15 mg/m <sup>3</sup> Total dust

#### 8.2. Exposure controls

Appropriate engineering controls : General ventilation. Local exhaust and enclosed processes may be necessary for processes which generate large quantities of airborne dust.

# Gillpatch III (Fiberglass Reinforced Cargoliner Patch)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Personal protective equipment	: An Appropriate apron or other body covering, see above, is recommended where there is a possibility of regular work clothing becoming contaminated with the product. All soiled or dirty clothing and personal protective equipment should be thoroughly cleaned before reuse.
Eye protection	: Where eye contact is possible with particulate matter, safety glasses with side shields are recommended.
Skin and body protection	: Use insulated, impervious plastic or neoprene-coated canvas gloves and protective gear (apron, face shield, etc.) to protect hands and other skin areas.
Respiratory protection	: Respiratory protection is not normally required. If appreciable dusts and/or particulate matter are generated during handling or processing, the operation should be evaluated by a professional industrial hygienist to determine the need for respiratory protection. If respiratory protection is deemed necessary, use, as a minimum, a respirator with NIOSH approvals for particulate matter. All provisions of OSHA's Respiratory Protection Standard (29 CFR 1910.134) should be followed. If exposure limits are exceeded or irritation is experienced, NIOSH approved respiratory protection should be worn.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Flat Sheet.
Color	: Brown in color on one side, white in color on the other side.
Odor	: Slight
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: 2.1
Solubility	: Unknown.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Product is stable. Hazardous polymerization will not occur.

### 10.3. Possibility of hazardous reactions

No additional information available

### 10.4. Conditions to avoid

No additional information available

# Gillpatch III (Fiberglass Reinforced Cargoliner Patch)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 10.5. Incompatible materials

Strong oxidizing agents, strong acids and bases, especially oxalic and hydrofluoric acid and acyl halides.

### 10.6. Hazardous decomposition products

CO, CO<sub>2</sub>, toxic phosphorus compounds, hydrogen fluoride, hydrogen cyanide and oxides of nitrogen.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed. Inhalation: dust/mist: Harmful if inhaled.

Gillpatch III (Fiberglass Reinforced Cargo liner Patch)	
ATE US (oral)	1470.588 mg/kg body weight
ATE US (dust, mist)	4.412 mg/l/4h

Flame Retardant (Proprietary)	
ATE US (oral)	500.000 mg/kg body weight

Skin corrosion/irritation : Causes severe skin burns and eye damage.  
Serious eye damage/irritation : Not classified  
Respiratory or skin sensitization : May cause an allergic skin reaction.  
Germ cell mutagenicity : Suspected of causing genetic defects (Dermal, Inhalation, oral).  
Carcinogenicity : May cause cancer (Dermal, Inhalation, oral).

Fiberglass (65997-17-3)	
IARC group	3 - Not classifiable
National Toxicology Program (NTP) Status	3 - Reasonably anticipated to be Human Carcinogen

Polyvinyl/fluoride polymer containing less than 0.025% nickel antimony titanium yellow pigment as nickel compounds (24981-14-4)	
IARC group	1 - Carcinogenic to humans
National Toxicology Program (NTP) Status	2 - Known Human Carcinogens

Reproductive toxicity : Not classified  
Specific target organ toxicity (single exposure) : Not classified  
Specific target organ toxicity (repeated exposure) : May cause damage to organs (lung/respiratory system) through prolonged or repeated exposure (Inhalation).  
Aspiration hazard : Not classified  
Symptoms/injuries : As packaged, this material does not present significant health hazards. The hazards below apply to the product if aerosols or dusts are generated from cutting, grinding, or smelting.  
Symptoms/injuries after inhalation : Inhalation of dust may result in itching and upper respiratory tract irritation.  
Symptoms/injuries after skin contact : Dusts and particulate matter may cause irritation of the skin.  
Symptoms/injuries after eye contact : Dusts and particulate matter may cause irritation of the eyes. Mechanical irritation, potentially severe, can result from eye contact with this material.  
Symptoms/injuries after ingestion : May cause toxic effects if inhaled or ingested/swallowed.  
Chronic symptoms : Persons with a history of chronic lung diseases may be at increased risk from exposure to excessive levels of nuisance dust. Persons with medical conditions generally aggravated by mechanical irritants in the air or on the skin may be at increased risk for a worsening of the underlying condition if exposed.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : This product has no known eco-toxicological effects.

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bio accumulative potential

No additional information available

# Gillpatch III (Fiberglass Reinforced Cargoliner Patch)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations : If material as supplied becomes a waste, incinerate or landfill in accordance with local, state, and federal laws and regulations. Incinerate only if incinerator is operated at high temperature and is capable of scrubbing out acidic combustion products. Contact your local or state environmental agency for specific rules.

Additional information : Empty containers will contain product residues. Observe proper safety and handling precautions. Do not allow empty containers to be used for any purpose except to store and ship original product.

Ecology - waste materials : Avoid release to the environment.

## SECTION 14: Transport information

In accordance with DOT  
Not regulated for transport

### Additional information

Other information : No supplementary information available.

### ADR

No additional information available

### Transport by sea

No additional information available

### Air transport

No additional information available

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### Gillpatch III (Fiberglass Reinforced Cargo liner Patch)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

All components of this product are listed on the Toxic Substances Control Act (TSCA) inventory except for:

Co-cured phenolic resin/synthetic elastomer( containing Methanol, Phenol, Formaldehyde)	CAS No Proprietary	C>=12.00% ; C<=14.00%
Intumescent adhesive coating	CAS No Proprietary	C>=35.00% ; C<=41.00%

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de Minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

#### Co-cured phenolic resin/synthetic elastomer (containing Methanol, Phenol, Formaldehyde) (Proprietary)

EPA TSCA Regulatory Flag	All components of this product are listed on the TSCA inventory.
--------------------------	--

### 15.2. International regulations

#### CANADA

No additional information available

#### Co-cured phenolic resin/synthetic elastomer( containing Methanol, Phenol, Formaldehyde) (Proprietary)

WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	--

### EU-Regulations

No additional information available

# Gillpatch III (Fiberglass Reinforced Cargoliner Patch)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**Classification according to Regulation (EC) No. 1272/2008 [CLP]**

**Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]**

Not classified

### 15.2.2. National regulations

### 15.3. US State regulations

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity

<b>Fiberglass (65997-17-3)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	

<b>Co-cured phenolic resin/synthetic elastomer (containing Methanol, Phenol, Formaldehyde) (Proprietary)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	

<b>Flame Retardant (Proprietary)</b>				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	

## SECTION 16: Other information

Revision date : 09/18/2015  
Data sources : ChemADVISOR, Inc.[<https://www.chemadvisor.com>]. ChemIDplus [<http://chem.sis.nlm.nih.gov/chemidplus/m/116094-23-6>]. GESTIS DNEL Database [[http://dnel-en.itrust.de/nxt/gateway.dll/dnel\\_en/000000.xml?f=templates\\$fn=default.htm\\$vid=dneleng\\$3.0](http://dnel-en.itrust.de/nxt/gateway.dll/dnel_en/000000.xml?f=templates$fn=default.htm$vid=dneleng$3.0)].



# Gillpatch III (Fiberglass Reinforced Cargoliner Patch)

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Full text of H-phrases:

Acute Tox. 4 (Inhalation: dust, mist)	Acute toxicity (inhalation: dust, mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Carc. 1A	Carcinogenicity Category 1A
Carc. 1B	Carcinogenicity Category 1B
Carc. 2	Carcinogenicity Category 2
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Flam. Liq. 2	Flammable liquids Category 2
Muta. 2	Germ cell mutagenicity Category 2
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Sens. 1	Skin sensitization Category 1
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
H225	Highly flammable liquid and vapor
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H332	Harmful if inhaled
H341	Suspected of causing genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H370	Causes damage to organs
H373	May cause damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life

### NFPA health hazard


: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

### NFPA fire hazard

: 0 - Materials that will not burn.

### NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



### HMIS III Rating

Health : 3 - Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given

Flammability : 0 - Minimal Hazard

Physical : 0 - Minimal Hazard

### SDS US (GHS HazCom 2012)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*