

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Product form : Mixture  
Product name : Sandwich Panels composed of Fiberglass Fabric-Reinforced Phenolic Facing Skins Bonded to A Nomex Aramid Honeycomb Core  
Other means of identification : GILLFAB 4004, 4004A, 4004B, 4123, 4223, 4322, 4323, 4522, 4523, 4623

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Use of the substance/mixture : Passenger flooring in high load areas such as entries, galleys and lavatories in commercial aircraft.

**1.3. Details of the supplier of the safety data sheet**

The Gill Corporation  
4056 Easy Street  
El Monte, CA 91731  
[www.thegillcorp.com](http://www.thegillcorp.com)

**1.4. Emergency telephone number**

Emergency number : CHEMTREC: 1-800-424-9300

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification (GHS-US)**

Carc. 1A H350  
STOT SE 1 H370

Full text of H-phrases: see section 16

**2.2. Label elements****GHS-US labeling**

Hazard pictograms (GHS-US) :



GHS08

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) :

H350 - May cause cancer (Inhalation)  
H370 - Causes damage to organs

Precautionary statements (GHS-US) :

P201 - Obtain special instructions before use  
P202 - Do not handle until all safety precautions have been read and understood  
P260 - Do not breathe dust/fume/gas/mist/vapors/spray  
P264 - Wash, hands and face thoroughly after handling  
P270 - Do not eat, drink or smoke when using this product  
P280 - Wear face protection, protective gloves  
P307 + P311 - If exposed: Call a poison center/doctor  
P308 + P313 - If exposed or concerned: Get medical attention  
P321 - Specific treatment (see Section 4 on this label)  
P405 - Store locked up  
P501 - Dispose of contents/container to comply with local/regional/national/international regulations

**2.3. Other hazards**

Other hazards not contributing to the classification : As packaged, this material does not present significant health hazards. The hazards below apply to the product if aerosols or dusts are generated from cutting, grinding, or smelting. Other constituents in this product are considered nuisance particles or dust. Exposure to dusts or powders may cause mechanical irritation of the respiratory system, eyes, and skin. This product contains trace amounts of Lead Chromate.

# Sandwich Panels composed of Fiberglass Fabric-Reinforced Phenolic Facing Skins Bonded to A Nomex Aramid Honeycomb Core

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 2.4. Unknown acute toxicity (GHS-US)

Not applicable

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Fiberglass	(CAS No) 65997-17-3	30 - 50	Carc. 1B, H350
Co-cured phenolic resin/synthetic elastomer( containing Methanol, Phenol, Formaldehyde)	(CAS No) Proprietary	27 - 40	Carc. 2, H351 STOT SE 1, H370
Cured Epoxy Adhesive	(CAS No) Proprietary	5 - 12	Comb. Dust, H232
Flame retardant	(CAS No) Proprietary	1 - 3	Carc. 1A, H350
Nomex Paper	(CAS No) 25765-47-3	5-23	Not classified

Full text of H-phrases: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

- First-aid measures general : Call 911 or emergency medical service. Move victim to fresh air. Keep victim warm and quiet. Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If exposed: Remove person to fresh air. If person is not breathing, provide artificial respiration. If necessary, provide additional oxygen once breathing is restored if trained to do so. Seek medical attention immediately.
- First-aid measures after skin contact : In case of burns, immediately cool affected skin for as long as possible with cold water. Do not remove clothing if adhering to skin.
- First-aid measures after eye contact : Immediately flush with large amounts of water, holding eyelids open, for at least 20 minutes. Repeat if necessary. Remove contact lenses, if present and easy to do. Seek medical assistance if irritation persists.
- First-aid measures after ingestion : Not an anticipated route of entry.

### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : As packaged, this material does not present significant health hazards. The hazards below apply to the product if aerosols or dusts are generated from cutting, grinding, or smelting.
- Symptoms/injuries after inhalation : Inhalation of dust may result in itching and upper respiratory tract irritation.
- Symptoms/injuries after skin contact : Dusts and particulate matter may cause irritation of the skin.
- Symptoms/injuries after eye contact : Dusts and particulate matter may cause irritation of the eyes. Mechanical irritation, potentially severe, can result from eye contact with this material.
- Symptoms/injuries after ingestion : May cause toxic effects if inhaled or ingested/swallowed.
- Chronic symptoms : Persons with a history of chronic lung diseases may be at increased risk from exposure to excessive levels of nuisance dust. Persons with medical conditions generally aggravated by mechanical irritants in the air or on the skin may be at increased risk for a worsening of the underlying condition if exposed.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

- Suitable extinguishing media : Any. Use media appropriate for surrounding fire.

### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Product will not burn.
- Reactivity : Not reactive under normal use and conditions.

### 5.3. Advice for firefighters

- Firefighting instructions : Evacuate area.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Firefighters should wear a NIOSH approved full-face piece self-contained breathing apparatus (SCBA) operated in positive pressure mode and full turnout or bunker gear.

# Sandwich Panels composed of Fiberglass Fabric-Reinforced Phenolic Facing Skins Bonded to A Nomex Aramid Honeycomb Core

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other information : If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also, consider initial evacuation for 800 meters (1/2 mile) in all directions.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protective equipment. Avoid dust formation. Avoid breathing vapors, mist or gas. Avoid breathing dust.

##### 6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

##### 6.1.2. For emergency responders

Protective equipment : Wear positive pressure self-contained breathing apparatus (SCBA). Wear protective clothing, a properly fitted, air-purifying or air-fed respirator if a risk assessment indicates this is necessary, chemical-resistant gloves, safety glasses.

Emergency procedures : Ventilate area.

#### 6.2. Environmental precautions

Any wastes generated during cleanup operations should be evaluated with respect to hazardous and solid waste regulations and disposed of in a properly permitted facility in accordance with all local, state, and federal regulations.

#### 6.3. Methods and material for containment and cleaning up

For containment : Do not walk through any dust resulting from damage to product. Prevent entry into waterways, sewers, basements or confined areas.

Methods for cleaning up : Pick up product and return to original packaging if reusable. If not reusable, place in appropriate containers for disposal. Any wastes generated during cleanup operations should be evaluated with respect to hazardous and solid waste regulations and disposed of in a properly permitted facility in accordance with all local, state, and federal regulations.

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with skin and eyes. Use methods to minimize dust. Do not breathe dust. DO NOT use compressed air or dry sweeping to remove dust from work area. Use a vacuum with adequate filtration system to remove dusts. If an appropriate vacuum is unavailable, only wet-clean-up methods should be used (i.e. misting). Moisture should be added as necessary to reduce exposure to airborne respirable dust.

Hygiene measures : Practice good housekeeping. Wash thoroughly after handling.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in tightly closed containers out of contact with the elements.

Incompatible products : Strong acids. reducing agents.

Packaging materials : Place carefully in dry, water-tight containers. Seal containers.

#### 7.3. Specific end use(s)

No additional information available

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Sandwich Panels composed of Fiberglass Fabric-Reinforced Phenolic Facing Skins Bonded to A Nomex Aramid Honeycomb Core		
ACGIH	Not applicable	
OSHA	Not applicable	
Fiberglass (65997-17-3)		
ACGIH	TLV	5 mg/m <sup>3</sup> total dust Resp dust 1 fiber/cc
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	3 fibers/cm <sup>3</sup> (fibers with diameter ≤ 3.5 μm & length ≥ 10 μm); 5 mg/m <sup>3</sup> TWA (total fibrous glass)
Cured Epoxy Adhesive (Proprietary) Particulates Not Otherwise Regulated		
ACGIH	Not applicable	

# Sandwich Panels composed of Fiberglass Fabric-Reinforced Phenolic Facing Skins Bonded to A Nomex Aramid Honeycomb Core

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Cured Epoxy Adhesive (Proprietary) Particulates Not Otherwise Regulated	
OSHA	Not applicable

Fire retardant ( containing phenol)		
ACGIH	TLV	5 mg/m <sup>3</sup> respdust
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup> resp dust

Co-cured phenolic resin/synthetic elastomer( containing Methanol, Phenol, Formaldehyde) (Proprietary)	
ACGIH	Not applicable
OSHA	Not applicable

Nomex Paper (25765-47-3)		
ACGIH	TLV	10 mg/m <sup>3</sup> total dust
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> total dust

Particulates Not Otherwise Regulated (Total Dust)		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	3 mg/m <sup>3</sup> Respirable; 10 mg/m <sup>3</sup> Total dust
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	5mg/m <sup>3</sup> Respirable; 15 mg/m <sup>3</sup> Total dust

### 8.2. Exposure controls

Appropriate engineering controls	: General ventilation. Local exhaust and enclosed processes may be necessary for processes which generate large quantities of airborne dust.
Personal protective equipment	: An Appropriate apron or other body covering, see above, is recommended where there is a possibility of regular work clothing becoming contaminated with the product. All soiled or dirty clothing and personal protective equipment should be thoroughly cleaned before reuse.
Eye protection	: Where eye contact is possible with particulate matter, safety glasses with side shields are recommended.
Skin and body protection	: Use insulated, impervious plastic or neoprene-coated canvas gloves and protective gear (apron, face shield, etc.) to protect hands and other skin areas.
Respiratory protection	: Respiratory protection is not normally required. If appreciable dusts and/or particulate matter are generated during handling or processing, the operation should be evaluated by a professional industrial hygienist to determine the need for respiratory protection. If respiratory protection is deemed necessary, use, as a minimum, a respirator with NIOSH approvals for particulate matter. All provisions of OSHA's Respiratory Protection Standard (29 CFR 1910.134) should be followed. If exposure limits are exceeded or irritation is experienced, NIOSH approved respiratory protection should be worn.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Sandwich panel.
Color	: brown
Odor	: Slight
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available

# Sandwich Panels composed of Fiberglass Fabric-Reinforced Phenolic Facing Skins Bonded to A Nomex Aramid Honeycomb Core

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Relative vapor density at 20 °C	: No data available
Relative density	: 0.3-0.5 g/cc
Solubility	: Unknown.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosive limits	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Not reactive under normal use and conditions.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

No additional information available

### 10.5. Incompatible materials

Strong oxidizing agents, strong acids and bases, especially oxalic and hydrofluoric acid and acyl halides.

### 10.6. Hazardous decomposition products

Decomposition and combustion products may be toxic. Can decompose in a fire emitting toxic fumes and gases of carbon dioxide, carbon monoxide, methane, formaldehyde, phenol, hydrogen cyanide, hydrogen bromide, oxides of nitrogen, small amounts of aromatic and aliphatic hydrocarbons; other toxic and irritating gases can be produced depending on condition of combustion.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

#### Flame retardant

LD50 oral rat	> 2000 mg/kg
---------------	--------------

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer (Inhalation).

#### Fiberglass (65997-17-3)

IARC group	3 - Not classifiable
National Toxicology Program (NTP) Status	3 - Reasonably anticipated to be Human Carcinogen

#### Flame retardant

IARC group	2B - Possibly carcinogenic to humans, 1 - Carcinogenic to humans
------------	--

Reproductive toxicity : Not classified

# Sandwich Panels composed of Fiberglass Fabric-Reinforced Phenolic Facing Skins Bonded to A Nomex Aramid Honeycomb Core

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Specific target organ toxicity (single exposure)	: Causes damage to organs.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Chronic symptoms	: Persons with a history of chronic lung diseases may be at increased risk from exposure to excessive levels of nuisance dust. Persons with medical conditions generally aggravated by mechanical irritants in the air or on the skin may be at increased risk for a worsening of the underlying condition if exposed.
Symptoms/injuries after skin contact	: Dusts and particulate matter may cause irritation of the skin. Contact with liquid on skin causes irritation and corrosion of tissue; continued exposure may cause dermatitis, chemical burns, and temporary loss of hair at site of contact.
Symptoms/injuries after eye contact	: Dusts and particulate matter may cause irritation of the eyes. Mechanical irritation, potentially severe, can result from eye contact with this material.
Symptoms/injuries after ingestion	: May cause toxic effects if inhaled or ingested/swallowed.
Chronic symptoms	: Persons with a history of chronic lung diseases may be at increased risk from exposure to excessive levels of nuisance dust. Persons with medical conditions generally aggravated by mechanical irritants in the air or on the skin may be at increased risk for a worsening of the underlying condition if exposed.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : This product has no known eco-toxicological effects.

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

No additional information available

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations : If material as supplied becomes a waste, incinerate or landfill in accordance with local, state, and federal laws and regulations. Incinerate only if incinerator is operated at high temperature and is capable of scrubbing out acidic combustion products. Contact your local or state environmental agency for specific rules.

Additional information : Empty containers will contain product residues. Observe proper safety and handling precautions. Do not allow empty containers to be used for any purpose except to store and ship original product.

Ecology - waste materials : Avoid release to the environment.

## SECTION 14: Transport information

In accordance with DOT  
Not regulated for transport

### Additional information

Other information : No supplementary information available.

### ADR

No additional information available

### Transport by sea

No additional information available

# Sandwich Panels composed of Fiberglass Fabric-Reinforced Phenolic Facing Skins Bonded to A Nomex Aramid Honeycomb Core

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Air transport

No additional information available

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### Sandwich Panels composed of Fiberglass Fabric-Reinforced Phenolic Facing Skins Bonded to A Nomex Aramid Honeycomb Core

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

All components of this product are listed on the Toxic Substances Control Act (TSCA) inventory except for:

Flame retardant	CAS No Proprietary	C $\geq$ 1.00% ; C $\leq$ 3.00%
Co-cured phenolic resin/synthetic elastomer( contain Methanol, Phenol, Formaldehyde)	CAS No Proprietary	C $\geq$ 27.00% ; C $\leq$ 40.00%
Nomex Paper	CAS No 25765-47-3	

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

#### Cured Epoxy Adhesive (Proprietary)

Listed on United States SARA Section 313

#### Co-cured phenolic resin/synthetic elastomer( containing Methanol, Phenol, Formaldehyde) (Proprietary)

EPA TSCA Regulatory Flag All components of this product are listed on the TSCA inventory.

### 15.2. International regulations

#### CANADA

No additional information available

#### Co-cured phenolic resin/synthetic elastomer( containing Methanol, Phenol, Formaldehyde) (Proprietary)

WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
----------------------	--

#### EU-Regulations

No additional information available

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

#### Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

### 15.2.2. National regulations

### 15.3. US State regulations

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity

#### Fiberglass (65997-17-3)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	

#### Co-cured phenolic resin/synthetic elastomer( containing Methanol, Phenol, Formaldehyde) (Proprietary)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	

# Sandwich Panels composed of Fiberglass Fabric-Reinforced Phenolic Facing Skins Bonded to A Nomex Aramid Honeycomb Core

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations


### SECTION 16: Other information

Revision date : 09/16/2015  
Data sources : ChemADVISOR, Inc.[<https://www.chemadvisor.com>]. ChemIDplus [<http://chem.sis.nlm.nih.gov/chemidplus/m/116094-23-6>]. GESTIS DNEL Database [[http://dnel-en.itrust.de/nxt/gateway.dll/dnel\\_en/000000.xml?f=templates\\$fn=default.htm\\$vid=dneleng:ddb eng\\$3.0/](http://dnel-en.itrust.de/nxt/gateway.dll/dnel_en/000000.xml?f=templates$fn=default.htm$vid=dneleng:ddb eng$3.0/)].

Full text of H-phrases:

Carc. 1A	Carcinogenicity Category 1A
Carc. 1B	Carcinogenicity Category 1B
Carc. 2	Carcinogenicity Category 2
Comb. Dust	Combustible Dust
STOT SE 1	Specific target organ toxicity (single exposure) Category 1
H232	May form combustible dust concentrations in air
H350	May cause cancer
H351	Suspected of causing cancer
H370	Causes damage to organs

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.  
NFPA fire hazard : 0 - Materials that will not burn.  
NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health : 3 Serious Hazard - Major injury likely unless prompt action is taken and medical treatment is given  
Flammability : 0 Minimal Hazard  
Physical : 0 Minimal Hazard

SDS US (GHS HazCom 2012)

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*