IE GILL CORPORATION

Fiberglass Reinforced Polyester Laminate

Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations Revision date: 06/27/2024 Supersedes: 05/1/2005

SECTION 1: Identification of the substance/mixture and of the company/undertaking **Product identifier** 1.1. Product form : Mixture Product name : Fiberglass Reinforced Polyester Laminate Product code 101 Other means of identification : Gilliner® 0990C Tan 1.2 Relevant identified uses of the substance or mixture and uses advised against Use of the substance/mixture : Cargo Liner 1.3. Details of the supplier of the safety data sheet The Gill Corporation 4056 Easy Street El Monte, CA 91731 (626) 443-4022 www.thegillcorp.com 1.4. **Emergency telephone number** Emergency number : THE GILL CORPORATION: 1-626-443-4022 CHEMTREC: 1-800-424-9300 **SECTION 2: Hazards identification** 2.1. **Classification of the substance or mixture Classification (GHS-US)** Carc. 1B H350 Full text of H-phrases: see section 16 2.2. Label elements **GHS-US** labeling Hazard pictograms (GHS-US) GHS08 Signal word (GHS-US) : Danger Hazard statements (GHS-US) : H350 - May cause cancer : P201 - Obtain special instructions before use Precautionary statements (GHS-US) P202 - Do not handle until all safety precautions have been read and understood P280 - Wear protective gloves, eye protection, protective clothing P308 + P313 - If exposed or concerned: Get medical advice/attention P501 - Dispose of contents/container to comply with local/regional/national/international

 Image: Provide the stands
 Provide the stands

 2.3. Other hazards
 Other hazards

 Other hazards not contributing to the classification
 : As packaged, this material does not present significant health hazards. The hazards below apply to the product if aerosols or dusts are generated from cutting, grinding, or smelting.

 2.4. Unknown acute toxicity (GHS-US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

3.2. **Mixture**

Name		Product identifier	%	Classification (GHS-US)
Fiberglass		(CAS No) 65997-17-3	50 - 80	Carc. 1B, H350
Cured polyester resin (containing styrene)		(CAS No) Not Available	20 - 50	Not classified
Full text of H-phrases: see section 16 S	pecific chemi	cal or percentage of chemical may be	withheld due to tr	ade secret.
SECTION 4: First aid measures				
.1. Description of first aid measure	es			
irst-aid measures general		er give anything by mouth to an uncor ice (show the label where possible).	scious person. If	you feel unwell, seek medical
irst-aid measures after inhalation		medical aid immediately. Remove fror athing, give artificial respiration. If brea		
irst-aid measures after skin contact		se immediately with large amounts of v rglass becomes imbedded, seek medio		b or scratch irritated area. If
irst-aid measures after eye contact		sh immediately with large amounts of v by from the eyeball to ensure thorough		
irst-aid measures after ingestion		expected to be an important route of e ter are ingested, it may cause gastroin		
.2. Most important symptoms and	effects, both	n acute and delayed		
symptoms/injuries		backaged, this material does not prese ly to the product if aerosols or dusts ar		
symptoms/injuries after inhalation		duct will act as a nuisance dust. Inhala ghing and mild, transitory respiratory ir		entrations of dust may cause
symptoms/injuries after skin contact	: Dus	ts and particulate matter may cause in	itation of the skin	I.
symptoms/injuries after eye contact	: Dus	ts and particulate matter may cause in	itation of the eye	s.
symptoms/injuries after ingestion		expected to be an important route of e duct may cause gastric discomfort or d		 Ingestion of large quantities of the
Chronic symptoms	exce	sons with a history of chronic lung dise essive levels of nuisance dust. Person chanical irritants in the air or on the ski erlying condition if exposed.	s with medical co	nditions generally aggravated by

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures	
5.1. Extinguishing media	
Suitable extinguishing media	: Any. Use media appropriate for surrounding fire.
5.2. Special hazards arising from the sub	ostance or mixture
Fire hazard	: Not flammable. Heat may cause flammable hazardous decomposition products, which may form toxic materials such as carbon dioxide, carbon monoxide, various low molecular weight hydrocarbons, oxides of phosphorus, biphenyl, organic acids and other toxic gases, acrid smoke, and fumes.
	Flammable gases and vapors may also be produced during thermal decomposition.
Reactivity	: Not reactive under normal use and conditions.
5.3. Advice for firefighters	
Protection during firefighting	: Positive pressure self-contained breathing apparatus (SCBA) and structural firefighters' protective clothing will provide adequate protection.

SECTION	SECTION 6: Accidental release measures		
6.1.	Personal precautions, protective equipment and emergency procedures		
General	neasures	: Evacuate area.	
6.1.1.	For non-emergency personnel		
Emergen	cy procedures	: Evacuate area.	
6.1.2.	For emergency responders		
Protectiv	e equipment	: Use personal protective equipment as required.	
Emergen	cy procedures	: Keep unauthorized personnel away.	
F201 - 6/1	8	EN (English US)	2/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

6.2. Environmental precautions

Avoid release to the environment.

6.3.	Methods and material for containn	ient and cleaning up	
For con	ntainment	: Do not walk through any dust resulting from damage to product.	
Methods for cleaning up		: Recover mechanically the product. Minimize generation of dust. HEPA Vacuum or wet methods and place in a disposal container.	
SECT	ION 7: Handling and storage		
7.1.	Precautions for safe handling		
_			

Precautions for safe handling	: Avoid contact with skin and eyes. Use methods to minimize dust Do not breathe dust. DO NOT use compressed air or dry sweeping to remove dust from work area. Use a vacuum with adequate filtration system to remove dusts. If an appropriate vacuum is unavailable, only wet- clean-up methods should be used (i.e. misting). Moisture should be added as necessary to reduce exposure to airborne dust.
Hygiene measures	: Practice good housekeeping. Wash thoroughly after handling. Change contaminated clothing. Do not reuse until laundered. Separate working clothes from town clothes. Launder separately.
7.2. Conditions for safe storage, inclu	iding any incompatibilities
Storage conditions	: Store in a well-ventilated place. Keep container tightly closed.
Incompatible products	: Strong acids, alkalis and oxidizers.
7.3. Specific end use(s)	

Cargo Liner

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Fiberglass (65997	-17-3)		
ACGIH	Not applicable		
OSHA	OSHA PEL (TWA) (mg/m³)	3 fibers/cm ³ (fibers with diameter \leq 3.5 µm & length \geq 10 µm); 5 mg/m3 TWA (total fibrous glass)	
Styrene (100-42-5)			
ACGIH	ACGIH TWA (ppm)	20 ppm	
ACGIH	ACGIH STEL (ppm)	40 ppm	
ACGIH	Remark (ACGIH)	CNS impair; URT irr; peripheral	
OSHA	OSHA PEL (TWA) (ppm)	100 ppm	
OSHA	Remark (OSHA)	(2) See Table Z-2.	
IDLH	US IDLH (ppm)	700 ppm	
Particulates Not Otherwise Regulated (Total Dust)			
ACGIH	ACGIH TWA (mg/m ³)	3 mg/m ³ Respirable; 10 mg/m ³ Total dust	
OSHA	OSHA PEL (TWA) (mg/m ³)	5mg/m ³ Respirable; 15 mg/m ³ Total dust	

8.2. **Exposure controls** Appropriate engineering controls : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Enclosed processes used in combination with local exhaust ventilation as necessary to control air contaminants at or below acceptable exposure guidelines. Collection systems must be designed and maintained to prevent the accumulation and recirculation of dust into the workplace. Hand protection : None normally needed. Impervious gloves may be used to prevent mechanical irritation. Where eye contact is possible with particulate matter, safety glasses with side shields are Eye protection recommended. Skin and body protection Depending on the risk, wear a tight, long apron and boots or suitable chemical protection clothing. Nitrile rubber or similar protection are recommended for waste clear-up and manufacturing operations. Respiratory protection : Follow NIOSH recommendations for respirator use if welding, cutting, or grinding.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 9: Physical and chemica	l properties
9.1. Information on basic physical and	I chemical properties
Physical state	: Solid
Color	: White (100G is green)
Odor	: Slightly Sweet
Odor threshold	: No data available
рН	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: 1.9 - 2.5 (H2O=1)
Solubility	: Insoluble in water.
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosive limits	: No data available
0.2 Other information	

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity			
10.1.	Reactivity		
Not reactive under normal use and conditions.			
10.2.	Chemical stability		
Stable under normal use and conditions.			
10.3.	Possibility of hazardous reactions		
Product is stable. Hazardous polymerization will not occur.			
10.4.	Conditions to avoid		
No additional information available			
10.5.	Incompatible materials		

Avoid contact with strong alkaline, strong mineral acids and oxidizing and reducing agents.

10.6. Hazardous decomposition products

Heat may cause flammable hazardous decomposition products, which may form toxic materials such as carbon dioxide, carbon monoxide, various low molecular weight hydrocarbons, oxides of phosphorus, biphenyl, organic acids and other toxic gases, acrid smoke, and fumes.

SECTION 11: Toxicological information		
11.1. Information on toxicological effects		
Acute toxicity : Not classified		
Cured polyester resin (containing styrene) (Not Available)		
LD50 oral rat	2650 mg/kg Science Reports of the Research Institutes, Tohoku University, Series C: Medicine. Vol. 36(1-4), Pg. 10, 1989.	

Safety Data Sheet according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Styrene (100-42-5)	
ATE US (gases)	4500.000 ppmV/4h
ATE US (vapors)	11.000 mg/l/4h
ATE US (dust, mist)	1.500 mg/l/4h
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: May cause cancer.
Fiberglass (65997-17-3)	
IARC group	3 - Not classifiable
National Toxicology Program (NTP) Status	3 - Reasonably anticipated to be Human Carcinogen
Styrene (100-42-5)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicology Program (NTP) Status	3 - Reasonably anticipated to be Human Carcinogen

National Toxicology Program (NTP) Status	3 - Reasonably anticipated to be Human Carcinogen
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	 Product will act as a nuisance dust. Inhalation of high concentrations of dust may cause coughing and mild, transitory respiratory irritation.
Symptoms/injuries after skin contact	: Dusts and particulate matter may cause irritation of the skin.
Symptoms/injuries after eye contact	: Dusts and particulate matter may cause irritation of the eyes.
Symptoms/injuries after ingestion	: Not expected to be an important route of entry into the body. Ingestion of large quantities of the product may cause gastric discomfort or distress.
Chronic symptoms	: Persons with a history of chronic lung diseases may be at increased risk from exposure to excessive levels of nuisance dust. Persons with medical conditions generally aggravated by mechanical irritants in the air or on the skin may be at increased risk for a worsening of the

underlying condition if exposed.

SECT	ON 12: Ecological information	1
12.1.	Toxicity	
No addi	tional information available	
12.2.	Persistence and degradability	
No addi	tional information available	
12.3.	Bioaccumulative potential	
No addi	tional information available	
12.4.	Mobility in soil	
No addi	tional information available	
12.5.	Other adverse effects	
Effect o	n the global warming	: No known ecological damage caused by this product.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations

: Recover or recycle if possible. Dispose in a safe manner in accordance with local/national regulations.

SECTION 14: Transport information

In accordance with DOT

Not regulated for transport

Additional information

Other information

: No supplementary information available.

ADR

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

15.1. US Federal regulations

Fiberglass (65997-17-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Cured polyester resin (containing styrene) (Not Available)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

Styrene (100-42-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313 CERCLA RQ 1000 lb

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

15.2.2. National regulations

styrene (100-42-5)

Listed on IARC (International Agency for Research on Cancer) Listed as carcinogen on NTP (National Toxicology Program)

15.3. US State regulations

Fiberglass (65997-17-3)				
U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

U.S California - Proposition 65 - Carcinogens List	U.S California - Proposition 65 - Developmental Toxicity	U.S California - Proposition 65 - Reproductive Toxicity - Female	U.S California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	27 µg per day

Styrene (100-42-5)

U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations

U.S. - Maine - Air Pollutants - Hazardous Air Pollutants U.S. - Massachusetts - Right To Know List

U.S. - Michigan - Critical Materials List

U.S. - New Jersey - Right to Know Hazardous Substance List

U.S. - New York - Reporting of Releases Part 597 - List of Hazardous Substances

U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information	
Revision date	: 06/27/2024
Data sources	 ChemADVISOR, Inc.[https://www.chemadvisor.com]. GESTIS DNEL Database [http://dnel- en.itrust.de/nxt/gateway.dll/dnel_en/000000.xml?f=templates\$fn=default.htm\$vid=dneleng:ddb eng\$3.0/].

Full text of H-phrases:

Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Carc. 1B	Carcinogenicity Category 1B
H302	Harmful if swallowed
H350	May cause cancer

NFPA health hazard


NFPA fire hazard

NFPA reactivity

: 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

: 0 - Materials that will not burn.

· 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health Flammability

Physical

: 1 Slight Hazard - Irritation or minor reversible injury possible

- : 0 Minimal Hazard
 - : 0 Minimal Hazard

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product